# **ICEMAKER | BLUI-150A**

L x D x H — 25" x 27<sup>3/4</sup>" x 38<sup>5/8</sup>"












Conforms to NSF/ANSI 7(ETL)

Project:		
Model#:		
Item #:		
Qty:		
Available W/H:		
Approval:		

### STANDARD FEATURES

- BLUI-150A produces up to 150 lbs. of ice daily
- BLUI-150A has 60 lbs. of built in storage capacity
- Units produce individual crescent ice cubes
- · Durable stainless steel cabinet
- · Stainless steel evaporator
- BLUI-150A equipped with slide in door
- · Removable air filter
- Digital Self Diagnostic System (power switch is accessible without panel removal)
- Optional built-in installation
- Environmentally friendly refrigerant (R-134A)
- Energy Star Certified

#### **Cube Dimensions\***



\*Approximate size in inches, image not to scale.

## **Operating Limits**

- Ambient Temp Range 45 100°F
- Water Temp Range 45 - 90°F
- Water Pressure 28 100 PSIG
- Voltage Range 100 - 130V

#### **Service**

- Panels easily removed and all components accessible for service.
- Removable/cleanable air filters.
- Allow 6" (15cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance/service.

### **Plumbing**


- Icemaker Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line:
  Minimum 3/4" Nominal ID
  Hard Pipe or Equivalent

\*BLUE AIR has the right to change specifications without further notice.


			ICE PRODUCTION								
Condenser	Model	Air / Water Temp Lbs. per 24 hours		Per Cycle		KWH per	Portable Water Gal.	Min. Circuit	Voltage	Shipping Weight	Energy Star®
		70°/50°F	90°/70°F	Lbs.	Cubes	100 lbs.	per 100 lbs.	Amperage		(lbs/kg)	<u> </u>
Air-Cooled	BLUI-150A	150	109	2.75	130	6	24	7	115V/60/1	143(65)	*



TOP VIEW



FRONT VIEW



SIDE VIEW

