

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

HORIZON TOP MOUNT REACH-IN

HF3HC Glass Triple Door Reach-In Freezer

Hydrocarbon Series

MODEL: HF3HC-1G



7 Year Parts/Labor Warranty 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior is stainless steel front and continuous coil coated sides
- Interior liner is made of corrosion resistant aluminum
- Full electronic control
- Expansion valve technology
- One piece grille
- LED interior light
- Self-closing door with 120° stay-open feature, on cam-lift hinges
- Snap-in magnetic gaskets for positive door seal
- Nine (9) heavy-duty epoxy coated wire shelves
- 6" Heavy-duty casters, two (2) with brakes
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- Tray slide pair, 1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (A)
- Stainless steel universal tray slide pair,1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (AC)
- Tray slide kit #4 (19 sets per half section)
- Additional epoxy shelves
- · Shelf clips
- Door locks
- Stainless steel breaker
- · 6" Legs seismic/flanged
- 3" Casters
- Remote option* (see note on back page)

FINISH OPTIONS

• HF Standard

(S/S front, continuous coil coated sides, aluminum interior)

(S/S front, S/S sides, aluminum interior)

HFS

(S/S front, continuous coil coated sides, S/S interior)

HFPS

(Complete S/S exterior & interior)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE &
- Hot gas condensate evaporator
- Adaptive defrost
- · Epoxy coated evaporator coil
- Freezer capable of maintaining product temperature down to -10°F









3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	HF3HC-1G	
EXTERNAL DIMENSIONAL DATA		
Width Overall	78"	
Depth Overall with Handle	33 %"	
Height Overall	85"	
Number of Doors	3	
Depth with Door Open 90°	55 ½"	
Door Openings (in)	21 %" x 61 ¾"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	69.1	
Internal Width Overall (in)	74"	
Internal Depth Overall (in)	25 1/8"	
Internal Height Overall (in)	62"	
Number of Shelves	9	
ELECTRICAL DATA		
Full Load Amperes 115/60/1**	13.2	
REFRIGERATION DATA		
Horsepower	(2) 3/4	
Capacity (BTU/Hr)	3854	
Heat Rejection (BTU/Hr)	5781	
Charge (lbs/grams/ounces)	0.2866 / 130 / 4.59	
SHIPPING DATA		
Gross Weight - Crated	760 lbs	
Height - Crated	88"	
Width - Crated	81"	
Depth - Crated	36"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.

** NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

Top Mount Reach-In Freezer Model: HF3HC-1G













