



ELEVATION SERIES CUBE ICE MAKER


CIMO826/O825

Ice-O-Matic
Ice. Pure and Simple

Model:

☐ CIMO826

☐ CIMO825



CIMO826 ON B42

Features and Benefits

- 22.25" (565 mm) wide space-saving design.
- Produces up to 922 lbs (418 kg) of ice per day.
- **Energy and Environment**
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- **Sanitation**
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- **Unique Dual Exhaust** - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- **Universal Smart Harness™** control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Ice Form

FULL CUBE DIMENSIONS	
W x D x H (in.)	7 7/8 x 7 7/8 x 7 7/8
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (in.)	3 7/8 x 7 7/8 x 7 7/8
W x D x H (mm)	10 x 22 x 22



CUBE

Bin Chart Kits for Combining Wider Bins with Smaller Models

ICE STORAGE BINS										
Model No.	B25	B40	B42	B55	B110	B700	B1000	B1300	B1325	B1660
Capacity	242 lbs (110 kg)	344 lbs (156 kg)	351 lbs (160 kg)	510 lbs (232 kg)	854 lbs (388 kg)	680 lbs (308 kg)	1,000 lbs (454 kg)	1,320 lbs (599 kg)	1,325 lbs (601 kg)	1,660 lbs (753 kg)
Width	30 in (762 mm)	30 in (762 mm)	22 in (559 mm)	30 in (762 mm)	48 in (1,219 mm)	30 in (762 mm)	48 in (1,219 mm)	48 in (1,219 mm)	60 in (1,524 mm)	60 in (1,524 mm)
Kits	KIT19		Kit Not Required	KIT19	N/A	Hold Down Securement Recommended				
CIMO826										
CIMO825										

*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIMO826	IFQI-XL	IOMQ (I)
CIMO825		

Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.

Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts
Evaporator (when enrolled in our filter program)	7 YEARS parts and labor




ELEVATION SERIES CUBE ICE MAKER

CIMO826/O825

Ice-O-Matic
Ice. Pure and Simple[®]


CIMO826/O825 CUBE ICE MAKER



Air Cooled

Please note: air-cooled units require 6" (152 mm) clearance for air intake and exhaust.

- A. Ice maker potable water in, $\frac{3}{8}$ " FPT.
- B. Ice maker water out, $\frac{3}{4}$ " FPT.
- C. Hole for electrical connections, $\frac{7}{8}$ ".
- D. Electrical connection junction box, $\frac{7}{8}$ ".



Remote Cooled

- A. Ice maker potable water in, $\frac{3}{8}$ " FPT.
- B. Ice maker water out, $\frac{3}{4}$ " FPT.
- C. Hole for electrical connections, $\frac{7}{8}$ ".
- D. Electrical connection junction box, $\frac{7}{8}$ " (remote).
- E. Condenser water in, $\frac{3}{8}$ " FPT (water only). Discharge line, $\frac{1}{2}$ " male quick connect coupling for precharged line set (remote only).
- F. Condenser water out, $\frac{1}{2}$ " FPT (water only).
- G. Liquid line, $\frac{3}{8}$ " male quick connect for precharged line set (remote only).

Operating Requirements

MINIMUM		MAXIMUM	
		60 Hz	50Hz
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)	110°F (43°C)
Water Temp.	40°F (4.4°C)		
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)	

Dimensions

ALL MODELS	
W x D x H (in.)	22.25 x 24.25 x 26.9
W x D x H (mm)	565 x 616 x 683

Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage gallons per 100 lbs of Ice 90°F air/70°F water		kWH Used per 100 lbs of ice @ 90°F air/ 70°F water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		70°F air/ 50°F water lbs (kg)	90°F air/ 70°F water lbs (kg)	Potable	Condenser					
CIMO826A	Air	896 (406)	711 (323)	19.0	N/A	5.0	208-230/60/1	11.8	20	15,100
CIMO826R**	Remote	906 (411)	793 (360)			4.9		12.3		
CIMO825A	Air	922 (418)	726 (329)	18.0		4.73	220-240/50/1	10.8	16	14,350
CIMO825R**	Remote	912 (414)	814 (369)			4.38		11.4		

* Daily ice production based on half cube configuration. When installing a CIM on a drink dispenser, the **KCUBEDISP** MUST be used.

** Remote models **CIMO826R** & **CIMO825R** require the **RCA-2061** remote condenser with optional grill guard kit.

Notes:

Number of Wires: 3 (including ground)

Approx. Shipping Weight lbs (kg): CIMO826A 220 (100) • CIMO826R 220 (100) • CIMO825A 220 (100) • CIMO825R 220 (100)

Refrigerant Type: R404A