

MODEL: **IUC-UC60F**

**UNDERCOUNTER:**  
**Undercounter Freezers**

### General Strengths

- ✓ **Energy efficiency higher.** R290 refrigerant with electric fans and evaporative tray without electric resistances.
- ✓ **Sanitation.** The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- ✓ **Doors.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in.
- ✓ **Control systems.** Greater ability for the adjustment of temperature range as per the end user's requirements.
- ✓ **100% Tested.** All condenser units are 100% tested, in helium chambers for refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)



UNIT TOTAL HEIGHT				
UNIT	LENGTH	DEPTH	2" CASTER HEIGHT	4" CASTER HEIGHT
IUC-UC60F	60-3/8	30-1/8	Optional	Standard
			32-11/16	35-3/4

MODEL	Dimensions (inches) (mm)			Nº Doors	Nº Shelves	Ref.	Ref. Weight (Lbs.) (gr.)	Temp. Range (°F) (°C)	Capacity (Cu. Ft.) (L)	Cond. Unit. H.P.	Case Amps 115 V.	Crated Weight (Lbs.) (Kg.)
	W	D	H									
IUC-UC60F	60-3/8 1533	30-1/8 765	35-3/4 910	2	4	R290	0.28 125	0°F -18°C	17 481	1/2	5.5	400 181

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

## MODEL: IUC-UC60F

## UNDERCOUNTER: Undercounter Freezers

### STANDARD FEATURES

#### ➤ Exterior

- AISI 430 Stainless Steel,
- AISI 304 Stainless Steel Top.

#### ➤ Interior

- AISI 430 Stainless Steel.

#### ➤ Doors

- Polyurethane insulated doors,
- Self closing doors with stay open feature,
- Stainless Steel heavy-duty hinges,
- Triple chamber snap in door gaskets for easy removal and cleaning,
- **Heated door frames to avoid accumulation of ice,**
- Full-height door opening: 25-5/8"x21-7/8" (650x555 mm).

#### ➤ Insulation

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in using a high-density polyurethane insulation,
- Low GWP & Zero ODP effect.

#### ➤ Shelving

- (2) Plastic coated wire shelves per section,
- Set of Stainless Steel shelf brackets,
- Easy remove for cleaning,
- Dimensions WxD: 27-1/4"x17" (692x432 mm).

#### ➤ Casters

- 4" diameter casters,
- Locks provided on front set.

#### ➤ Refrigeration

- Temperature regulated by thermostatic control,
- Temperature display,
- Hot gas defrost,
- Energy-saving non-electric condensate pan,
- Evaporator coil coated with anti-corrosion material 100% Polyester,
- Forced air refrigeration system,
- Expansion valve,
- Electric fans,
- Refrigeration capacity: 1696 Btu/h (-22°F) / 497 W (-30°C).

#### ➤ Electrical

- Cord and NEMA 5-15P plug.
- Electrical connection is 115V / 1ph / 60 Hz.
- 20 AMP breakers required,




#### ➤ ETL Listed to UL471 Standard and Sanitation classified to NSF7.

### OPTIONAL FEATURES

- ✓ Single Overshelf kit.
- ✓ Double Overshelf kit,
- ✓ 4" Backsplash,
- ✓ Set of 2" diameter casters, with lock provided on front set,
- ✓ Electrical connection is 230 V / 1ph / 50 Hz (plug type varies).

### PLAN VIEW



ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE